



## Mr Oil

Synthetic Blend Heavy-Duty Engine Oils  
SAE 20W-50 API CJ-4/SN

### Product Description

**Mr Oil** Synthetic Blend Heavy-Duty Engine Oil, **SAE 20W-50, API CJ-4/SN** parasyntetic crankcase lubricants for use in modern diesel engines. Formulated with a blend of synthetic and conventional base oil as well as a premium quality additive package, this oil exhibits excellent detergent, dispersant, anti-wear, anti-corrosion, anti-oxidant, and anti-foaming properties.

### Typical Properties\*

<b>SAE J300 Viscosity Grade</b>	<b>20W-50</b>
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	160.55
Viscosity @ 100°C, cSt, ASTM D445	18.5
Viscosity Index, ASTM D2270	130
CCS Apparent Viscosity, cP, ASTM D5293	6,250@-15°C
Flash Point, °C, ASTM D92	225
Pour Point, °C, ASTM D97	-30
Total Base Number, mg KOH/g, ASTM D2896	9

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

### **Exceeds Performance Requirements**

API CJ-4, CI-4 Plus, CI-4, CH-4, CF-4, CF-2, CF  
API SN, SM, SL, SJ, SGF