



Mr Oil

SAE 5W-30 Full Synthetic Motor Oil
API SP, API SN ILSAC GF-6A, GF-5

Product Description

Mr Oil SAE 5W-30 is a premium full synthetic motor oil manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

This oil is formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

SAE J300 Viscosity Grade	5W-30
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	61.25
Viscosity @ 100°C, cSt, ASTM D445	10.8
Viscosity Index, ASTM D2270	170
CCS Apparent Viscosity, cP, ASTM D5293	5,200@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-35°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-42

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

Exceeds Performance Requirements

API SP with Resource Conserving, API SN Plus, API SN
ILSAC GF-6A, GF-5
GM dexos1™ Gen 2
Chrysler MS6395
Ford WSS-M2C946-B1 (5W-30)