



Mr Oil Antifreeze (High Performance Antifreeze)

Product Description

Mr Oil Antifreeze is a high performance antifreeze formula that is available in both concentrated and pre diluted packing

Features and Benefits

Mr Oil Antifreeze contains Mono Ethylene Glycol and helps to prevent winter freezing and summer overheating.

Applications

Mr Oil Antifreeze is recommended for use in applications requiring BS6580-1992 quality standard.

For concentrated Mr Oil Antifreeze Water Specifications

- Hardness, °dGH (mmol/l) 0 - 20 (0 - 3.6)
- Chloride Content, ppm max 100
- Sulphate Content, ppm max 100

Dilution Table

Antifreeze	Water	Freeze protection
33 %	67 %	-18°C
50 %	50 %	-36°C
60 %	40 %	-52°C

Specifications and Approvals

Mr Oil Antifreeze is recommended for use in applications requiring the following industry specification:

BS6580-1992

Gas Vol	1 Gal	2 Gal	3 Gal	4 Gal	5 Gal	6 Gal
Gas : Oil	Oz	Oz	Oz	Oz	Oz	Oz
16 : 1	8	16	24	32	40	48
20 : 1	6	13	19	26	32	38
24 : 1	5	11	16	21	27	32
25 : 1	5	10	15	20	26	31
40 : 1	3	6	10	13	16	19
50 : 1	3	5	8	11	13	16