



**Mr Oil**  
Synthetic Multi-Vehicle ATF

### Product Description

Formulated with synthetic base stocks and premium performance additives, **Mr Oil SYNTHETIC MULTI-VEHICLE ATF** is a premium grade low viscosity synthetic automatic transmission lubricant. This product contains a premium performance additive package designed for excellent oxidation stability and thermal resistance as well as excellent friction modification properties. **Mr Oil SYNTHETIC MULTI-VEHICLE ATF** is a multipurpose automatic transmission lubricant which is suitable for use in applications which require GM DEXRON® VI as well as a variety of North American, Asian and European passenger car applications requiring low viscosity ATF.

### Typical Properties\*

<u>Parameter</u>	<u>Result</u>
<u>Appearance, Visual</u>	<u>Red, Dyed Liquid</u>
<u>Viscosity @ 40°C, cSt, ASTM D445</u>	<u>29.5</u>
<u>Viscosity @ 100°C, cSt, ASTM D445</u>	<u>6.0</u>
<u>Viscosity Index, ASTM D2270</u>	<u>155</u>
<u>Brookfield Viscosity @-40°C, ASTM D2983, cP</u>	<u>12,000</u>
<u>Flash Point, °C, ASTM D92</u>	<u>190</u>
<u>Pour Point, °C, ASTM D97</u>	<u>-52</u>

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

### **Suitable for Use**

- Ford MERCON®\*, MERCON® V\*, MERCON® SP\*, MERCON® LV\*
- General Motors DEXRON®-II(E), DEXRON-III(G,H), DEXRON-VI
- BMW LT 71141, LA2634, M-1375.4, 7045-E, ETL-8072B •Chrysler ATF +3 (SM7176-E)\*, ATF +4 (MS9602)\*
- Aisin Warner AW-1
- Honda/Acura DW-1, ATF-Z1
- Hyundai/Kia/Mitsubishi Diamond SP, SP-II, SP-III
- Isuzu ATF-II, ATF-III, Genuine ATF
- Mazda ATF 3317, F-1, FZ/S-1/N-1, M-III, M-V
- MB 236.12\*, MB 236.14\*, MB 236.15\*
- Nissan 402, Matic D/J/K/S
- Allison TES-389\*, C-4
- Hyundai/Kia SP-IV, SPH-IV/SP4-M
- Idemitsu ATF HP, K17
- JASO M315 Class 1A\* and 2013, 1A-LV
- MB 236.41/5/6/7/8/9/91/10/11, NAG-1
- Mitsubishi ATF-J2, ATF-J3
- Subaru ATF, ATF 5AT, ATF-HP